

pitch diamètre primitif Wirkdurch- messer diametro primitivo dw [mm]	grooves gorges Rillen canales N°	taper bush moyeux amovibles Spannbuchse casquillo conico		size forme Ausführung forma fig.	M [mm]	L [mm]	Z [mm]	U [mm]	weight poid Gewicht peso [kg]
		type type Typ tipo	bore alésage Bohrung bujie min-max d [mm]						
200	1	2012	15-50	4	110	31	11	167	3,16
	2	2517	18-65	4	120	46	11	167	4,70
	3	2517	18-65	5	120	46	4	167	5,36
	4	3020	25-75	5	146	51	14	167	8,20
	5	3020	25-75	6	146	51	14,5	167	8,40
224	1	2012	15-50	4	110	31	11	191	3,42
	2	2517	18-65	4	120	46	11	191	5,68
	3	2517	18-65	6	120	46	2	191	5,90
	4	3020	25-75	5	146	51	14	191	8,20
	5	3020	25-75	5	146	51	29	191	9,06
236	1	2012	15-50	4	110	31	11	203	3,64
	2	2517	18-65	4	120	46	11	203	5,09
	3	2517	18-65	5	120	46	4	203	6,30
	4	3020	25-75	6	146	51	7	203	8,24
	5	3020	25-75	6	146	51	14,5	203	9,46
250	1	2012	15-50	4	110	31	11	217	4,14
	2	2517	18-65	4	120	46	11	217	6,03
	3	2517	18-65	6	120	46	2	217	7,92
	4	3020	25-75	6	146	51	7	217	8,28
	5	3020	25-75	6	146	51	14,5	217	10,15
280	1	2012	15-50	7	110	31	11	247	4,40
	2	2517	18-65	7	120	46	11	247	6,70
	3	2517	18-65	6	120	46	2	247	7,90
	4	3020	25-75	6	146	51	7	247	11,15
	5	3020	25-75	9	146	51	14,5	247	11,20
315	1	2012	15-50	7	110	31	11	282	4,40
	2	2517	18-65	7	120	46	11	282	6,56
	3	3020	25-75	3	146	51	0,5	282	8,56
	4	3020	25-75	9	146	51	7	282	9,64
	5	3020	25-75	9	146	51	14,5	282	13,00
355	1	2012	15-50	7	110	31	11	322	5,50
	2	2517	18-65	7	120	46	11	322	7,97
	3	3020	25-75	3	146	51	0,5	322	10,40
	4	3020	25-75	9	146	51	7	322	14,44
	5	3020	25-75	9	146	51	14,5	322	15,66
400	1	2012	15-50	7	110	31	11	367	6,72
	2	2517	18-65	7	120	46	11	367	9,08
	3	3020	25-75	3	146	51	0,5	367	12,28
	4	3020	25-75	9	146	51	7	367	15,40
	5	3020	25-75	9	146	51	14,5	367	17,02
450	1	2517	18-65	7	120	46	26	417	8,20
	2	2517	18-65	7	120	46	11	417	10,52
	3	3020	25-75	3	146	51	0,5	417	13,42
	4	3020	25-75	9	146	51	7	417	16,82
	5	3020	25-75	9	146	51	14,5	417	20,50
500	1	2517	18-65	7	120	46	26	467	10,48
	2	2517	18-65	7	120	46	11	467	12,90
	3	3020	25-75	3	146	51	0,5	467	16,90
	4	3020	25-75	9	146	51	7	467	19,80
	5	3020	25-75	9	146	51	14,5	467	23,10
560	1	3020	25-75	7	146	51	31	527	14,80
	2	3020	25-75	7	146	51	16	527	19,00
	3	3020	25-75	7	146	51	1	527	23,94
	4	3020	25-75	8	146	51	14	527	32,00
	5	3535	45-90	7	178	91	11	527	40,00
630	1	3020	25-75	7	146	51	31	597	17,00
	2	3020	25-75	7	146	51	16	597	21,52
	3	3020	25-75	7	146	51	1	597	25,78
	4	3020	25-75	8	146	51	14	597	32,78
	5	3535	45-90	7	178	91	11	597	44,60
800	3	3535	45-90	7	178	91	41	767	41,00
	4	3535	45-90	7	178	91	26	767	50,00
	5	3535	45-90	7	178	91	11	767	52,50
1000	3	3535	45-90	7	178	91	41	967	50,00
	4	4040	55-100	7	215	101	36	967	68,00
	5	4040	55-100	7	215	101	21	967	74,00




fig. 1




fig. 2




fig. 3




fig. 4




fig. 5




fig. 6




fig. 7




fig. 8




fig. 9




fig. 10




fig. 11